


Merk: **APart**

Model: CM20DT



## Omschrijving

6.5" two-way, thin edge ceiling loudspeaker, white

The CM20DT 6.5" two-way built-in loudspeaker can be used in 16 ohms or 70/100 volt modes. The high-quality 70/100 volt transformer is equipped with an easy tapping sticker with clear colour indication. The transformer colours are aligned with the cables connecting the Apart Quick Fit connector, a handy installer connector via push terminal. In 16 ohms use, you can connect up to 4 loudspeakers in parallel on each channel of a standard 4 ohms amplifier. The paintable thin edge grille makes CM20DT the ultimate loudspeaker for design interior integration.

## Specificaties

### ALGEMEEN

|                                |           |                                  |      |
|--------------------------------|-----------|----------------------------------|------|
| Aantal luidsprekers in de doos | 1 speaker | Totaal uitgangsvermogen (muziek) | 30 W |
| Type speaker                   | Inbouw    |                                  |      |

### AUDIO

|                  |               |
|------------------|---------------|
| Frequentiebereik | 60 - 20000 Hz |
|------------------|---------------|

### FYSIEKE KENMERKEN

|         |            |        |            |
|---------|------------|--------|------------|
| Breedte | 21, 186 cm | Diepte | 8, 80 cm   |
| Gewicht | 1,24 kg    | Hoogte | 186, 21 mm |
| Kleur   | Wit        |        |            |

**LUIDSPREKEROPBOUW**

|                 |        |                    |       |
|-----------------|--------|--------------------|-------|
| Actieve speaker | Nee    | Diameter tweeter   | 25 mm |
| Diameter woofer | 165 mm | Luidsprekerfilters | 2-weg |

**LUIDSPREKERPRESTATIES**

|              |       |            |        |
|--------------|-------|------------|--------|
| Gevoeligheid | 86 dB | Impedantie | 16 ohm |
|--------------|-------|------------|--------|