

Merk: **KEF**

Model: SP3927AA



Omschrijving

Features KEF's patented Uni-Q driver array

With a 38mm(1.5inch) tweeter voice coil coupled to a vented aluminium dome with tangerine waveguide, and a woofer with absolutely massive magnet and Z-flex surround, the KEF Ci200RS-THX is capable of delivering a magical musical theatre experience even in the largest of rooms.

Ci200RS-THX

For the ultimate Extreme Home Theatre, the Ci-R Series has the outstanding acoustic capabilities of the KEF floorstander it's named after, with all the drama and emotional intensity of full theatre sound quality.

With a 38mm(1.5inch) tweeter voice coil coupled to a vented aluminium dome with tangerine waveguide, and a woofer with absolutely massive magnet and Z-flex surround, the KEF Ci200RS-THX is capable of delivering a magical musical theatre experience even in the largest of rooms.

GRILLE ON

Ci200RS-THX is an in-wall speaker certified to THX ULTRA2 standard. A deep understanding of the filmmaking process and surround sound is at the very heart of every THX certified 2.1, 5.1 and 7.1 speaker system. Engineered with design characteristics of professional studio speakers, THX recreates the tonal balance of the filmmaker's final mix in your living room. The results? Action sequences are impactful, and dialogue-driven moments are natural and engaging.

THX certified in-wall speakers deliver the appropriate frequency response and high output and imaging quality of a traditional box speaker. This provides the best of both worlds - THX surround sound performance from components that blend harmoniously with any room decor.

Specificaties

ALGEMEEN

Aantal luidsprekers in de doos	1 speaker	Type speaker	Inbouw
--------------------------------	-----------	--------------	--------

AUDIO

Frequentiebereik	33 - 28000 Hz
------------------	---------------

FYSIEKE KENMERKEN

Breedte	24 cm	Gewicht	3,6 kg
Hoogte	24 cm		

LUIDSPREKEROPBOUW

Diameter tweeter	38 mm	Diameter woofer	200 mm
Ingebouwde tweeter	Ja	Ingebouwde woofer	Ja

LUIDSPREKERPRESTATIES

Aanbevolen versterker vermogen	10 - 190 W	Gevoeligheid	90 dB
Impedantie	4 ohm		